

TVC-22VRLP

HD TVI POC IR DOME




KEY FEATURES

- 2.0 megapixel high performance CMOS
- 1920 X 1080 resolution
- 2.8 mm to 12 mm vari-focal lens
- True Day/Night
- Up to 30 m IR distance
- PoC.af
- Up the coax



SPECIFICATION	TVC-22VRLP
Camera	
Image Sensor	2 MP progressive scan CMOS
Signal System	PAL/NTSC
Frame Rate	PAL: 1080p@25fps
Resolution	1920 (H) × 1080 (V)
Min. illumination	0.01 Lux@(F1.2, GC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s
Lens	2.8 mm to 12 mm
Horizontal Field of View	105.2 ° to 32.8 °
Lens Mount	Φ14
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 340°, Tilt: 0° to 75°, Rotation: 0° to 355°
Synchronization	Internal synchronization
Menu	
AGC	Low/middle/high
Day/Night Mode	Smart/color/BW(Black and White)
Backlight Compensation	Yes
DWDR	Yes
Language	English
Functions	Brightness, Sharpness, DNR, Mirror
Interface	
Video Output	1 HD analog output/1 Vp-p composite output (75Ω/BNC)
General	
Operating Conditions	-40 °C to 60 °C, humidity: 90% or less (non-condens.)
Power Supply	12 VDC ±15%/PoC.af
Power Consumption	Max. 4 W
Material	Plastic
IR Range	Up to 30 m
Dimensions	Ø 136 mm × 102 mm
Weight	600 g



DIMENSIONS:

