

HAVR-04LT HAVR-08LT HAVR-16LT

HAVR - TVI/AHD/960H




KEY FEATURES

- Connectable to HD-TVI, AHD, network and analog cameras
- H.264 ,H.264+ & Dual-stream video compression
- Support HD-TVI, AHD and analog cameras with adaptive access
- Support 1080P lite mode enabled to realize the real-time 1080P lite and 720P lite resolution
- HDMI and VGA output at up to 1920 1080P resolution
- Long transmission distance over coax cable
- Up to 4/8/16-ch synchronous playback at 1080p resolution
- playback at up to 256X speed.



SPECIFICATION	HAVR-04LT	HAVR-08LT	HAVR-16LT
Video/Audio Input			
Video compression	H.264+/H.264		
Analog video input	4-ch	8-ch	16-ch
	BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection		
Supported HD TVI input	1080p/25Hz, 1080p/30Hz, 720p/25Hz, 720p/30Hz, 720P/50Hz, 720p/60Hz		
Supported AHD input	720p/25Hz, 720p/30Hz		
CVBS input	Support		
IP video input	1-ch	2-ch	2-ch
	Up to 2.0 MP resolution		
Audio compression	G.711u		
Audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)		
Video/Audio output			
CVBS output	Support		
HDMI/VGA output	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60Hz, 1024 × 768/60 Hz	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60Hz, 1024 × 768/60 Hz	
Encoding resolution	When 1080p Lite mode not enabled: 1080p(non-real-time)/720p/VGA/WD1/4CIF/CIF; When 1080p Lite mode enabled: 1080p lite/720p lite/VGA/WD1/4CIF/CIF		
Frame rate	Main stream: 1/16 fps to real time frame rate Sub-stream: WD1/4CIF@12fps/2CIF (non-real-time); CIF/QVGA/QCIF (real time)		
Video bit rate	32 Kbps to 6 Mbps		
Audio output	1-ch, RCA (Linear, 1 KΩ)		
Audio bit rate	64 Kbps		
Dual-stream	Support;		
Stream type	Video, Video & Audio		
Synchronous playback	4-ch	8-ch	16-ch
Network management			
Remote connections	128		
Network protocols	TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF		
Hard disk			
SATA	1	2	
Capacity	Up to 6TB capacity		
External interface			
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the audio input)		
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface	
General			
Power supply	12 VDC		
Consumption (without HDD)	≤ 15 W	≤ 20 W	≤ 30 W
Working temperature	-10 °C to +55 °C		
Working humidity	10% to 90%		
Dimensions	315 × 242 × 45 mm		
Weight (without HDD)	≤ 2 kg		

Rear Panel of HAVR-04LT



- 1 VIDEO IN
- 2 VIDEO OUT
- 3 AUDIO IN, RCA Connector
- 4 AUDIO OUT, RCA Connector
- 5 VGA Interface
- 6 HDMI Interface
- 7 USB Interface
- 8 LAN Network Interface
- 9 RS-485 Serial Interface
- 10 12VDC Power Input
- 11 Power Switch
- 12 GND