

Codice articolo: 1977-SFOG-P1500-U**Descrizione del prodotto:** sistema igienizzante plus

Caratteristiche principali: Sistema igienizzante potente e veloce, ideale per proteggere grandi aree come grandi negozi, depositi, ipermercati o anche per proteggere obiettivi in spazi aperti. Emette, in un unico sparo, fino a 750 m³ di fitta nebbia in 70 secondi. E' dotato di una sacca di liquido (igienizzante Sani-FOG) ed è predisposto per l'utilizzo anche come nebbiogeno igienizzante (con sacca Dual-FOG, opzionale) ed una facile installazione a parete.



CARATTERISTICHE TECNICHE

- Alimentazione: 230 Vca
- Consumo medio: 60 W
- Batteria di backup: presente
- Sistema di riscaldamento: Plus
- Copertura in un singolo sparo con funzionalità di igienizzante:
 - con sacca Sani-FOG: fino a 750 m³
 - con sacca Dual-FOG: fino a 1.500 m³
- Copertura in un singolo sparo con funzionalità di nebbiogeno antintrusione:
 - Con sacca Sani-FOG: non applicabile
 - Con sacca Dual-FOG (visibilità raccomandata): fino a 2.000 m³
 - Con sacca Dual-FOG (visibilità 1,5 m): fino a 1.500 m³
- Tempo max di emissione in un singolo sparo: 70 s
- Capacità totale di emissione con sacca carica:
 - con sacca Sani-FOG: 750 m³
 - con sacca Dual-FOG: 1.500 m³
- Numero di sacche incluse: 1
- Quantità di liquido nella sacca: 1.000 ml
- Caratteristiche dello sparo: programmabile in secondi
- Antimanomissione dell'ugello: presente
- Interfaccia seriale: presente
- Protocollo di comunicazione: standard
- Tempo di autonomia senza rete elettrica: > 2,5 h
- Tempo di riscaldamento da freddo: ~ 2 h
- Montaggio verticale: possibile
- Montaggio orizzontale: opzionale
- Materiale: acciaio
- Peso: 29 kg
- Dimensioni: 285 x 360 x 435 mm

ACCESSORI DISPONIBILI

- **1981-D-FBP1000** • Fluid bag Dual-FOG da 1.000 ml per modello Power
- **1983-S-FBP1000** • Fluid bag Sani-FOG da 1.000 ml per modello Power

**BS OHSAS 18001:2007**
Occupational Health and
Safety Management System**ISO 14001:2015**
Environmental Management
System**ISO 9001:2015**
Quality Management
System**CI ITP: 2015**
100% Made in Italy
Certificate

LINCE ITALIA S.p.A.

Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586www.lincede.net - info@lincede.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

Item Code: 1977-SFOG-P1500-U**Product description:** Hygienizing system plus

Main features: Powerful and fast hygienizing system plus, ideal for protecting large areas such as large shops, stores, supermarkets or even for protecting targets in open spaces. In a single shot it provides up to 1,500 m³ of dense fog in 70 seconds. It is equipped with a removable fluid bag (hygienizing liquid, Sani-FOG) and is designed to be used also as hygienizing fogging system (with Dual-FOG fluid bag, optional) and for easy wall installation.



SPECIFICATIONS

- Power supply: 230 Vac
- Average consumption: 60 W
- Backup battery: present
- Heating system: Plus
- Coverage in a single shot with hygienizing functionality
 - with Sani-FOG fluid bag: up to 750 m³
 - with Dual-FOG fluid bag: fino a 1.500 m³
- Coverage in a single shot with fogging functionality
 - with Sani-FOG fluid bag: not applicable
 - with Dual-FOG fluid bag (1.5 m visibility): up to 2,000 m³
 - with Dual-FOG fluid bag (recommended visibility): up to 1,500 m³
- Max emission time in a single shot: 70 s
- Total emission capacity with loaded bag:
 - with Sani-FOG fluid bag: up to 750 m³
 - with Dual-FOG fluid bag: fino a 1,500 m³
- Number of bags included: 1
- Quantity of liquid in the bag: 1,000 ml
- Shooting characteristics: programmable in seconds
- Nozzle anti-tamper: present
- Serial interface: present
- Communication protocol: standard
- Autonomy time without mains: > 2.5 h
- Heating time from cold: ~ 2 h
- Vertical mounting: possible
- Horizontal mounting: optional
- Cabinet material: steel
- Weight: 29 kg
- Dimensions: 285 x 360 x 435 mm

AVAILABLE ACCESSORIES

- **1981-D-FBP1000** • 1,000 ml Dual-FOG fluid bag for Power model
- **1983-S-FBP1000** • 1,000 ml Sani-FOG fluid bag for Power model

**BS OHSAS 18001:2007**
Occupational Health and
Safety Management System**ISO 14001:2015**
Environmental Management
System**ISO 9001:2015**
Quality Management
System**CI ITP: 2015**
100% Made in Italy
Certificate

LINCE ITALIA S.p.A.

Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586www.lince.net - info@lince.net
MD-03.11 Rev. 6 - Pag.: 2 di 2