

# IWN-22VR

IP BULLET



## KEY FEATURES

- High performance Sony CMOS, 2M, 1080P
- Audio, hardware reset, waterproof RJ45
- H.264 ,dual-stream
- Max resolution:1920\*1080
- Onvif and P2P supported
- IR Cut Filter
- 3pcs IR Array up to 30 meter
- IP66
- 2.8-12mm lens



SPECIFICATION	IWN-22VR
Sensor	1/2.9" SONY CMOS
Min Illumination	Color 0.1Lux@F1.2,white/black 0.01 Lux@F1.2
WDR Range	dWDR Range >80db
Video processing	H.264, dual-stream, CBR/VBR, 32K~16M bit/S adjustable, 1-30fps adjustable
Main stream	1920*1080, 1280*720
Sub stream	720*576, 640*480, 640*352, 320*240
Audio interface	Support 1 channel linear audio input, 1channel audio output
Audio processing	G.711 coding Standard, Support both way Voice intercom function, support the synchronization of audio and video
Network protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP;
IR linkage	support
Reset interface	support
Alarm input	1channel input,Low Level effective
Alarm output	1 Channel IO Output
Operation function	Support Web setting,OSD,real-time video transmission,support motion detection and IO alarm linkage for front end shortage/Capture,Support Central remind and image linkage after motion detection and IO alarm linkage,support MJPEG capture,Support unit client-side remote management software, provide complete SDK
Standard protocol	Onvif 2.4
Mobile monitor	Support P2P, (IOS, Android)
Power supply	DC10.8V~13.2V, PoE 650mA
Working temperature	-20C~55C
Protection rate	ESD 1kv
IR Series Distance	Max. 30 Meter with 3pcs IR Array
Lens	2.8-12mm lens
Camera size	277.5mm(L)*79MM(H)



## DIMENSIONS

