

HXVR-04E101H1



Features and Functions

Key features

- | H.264+/H.264 video compression
- | HDTV/AHD/CVI/CVBS/IP video input
- | Up to 5-ch IP camera input for (up to 1080p)
- | Max. 1200 m for 720p HDTV signal

Compression and Recording

- | H.264 + video compression improves encoding efficiency and reduces data storage costs
- | Support 1080p lite of all channels. When 1080p lite is on, the image effect is similar with 1080p

Storage and Playback


- | One SATA interface (up to 6 TB capacity per HDD)
- | Smart search for efficient playback

Network & Ethernet Access

- | CTR-MAZi and DDNS (Dynamic Domain Name System) for easy network management
- | Mbps total bandwidth

Model		HXVR-04E101H1	
Recording	Video compression	H.264+/H.264	
	Encoding resolution	When 1080p Lite mode not enabled: 720p/WD1/4CIF/VGA/CIF When 1080p Lite mode enabled: 1080p lite/720p/WD1/4CIF/VGA/CIF	
	Frame rate	<i>Main stream:</i> When 1080p Lite mode not enabled: For 720p stream access: 720p/WD1/4CIF/VGA/CIF @ 25fps (P)/30fps (N) When 1080p Lite mode enabled: 1080p lite/720p/WD1/4CIF/VGA/CIF @ 25fps (P)/30fps (N) <i>Sub-stream:</i> 2CIF @ 6fps; CIF/QVGA/QCIF @ 25fps (P)/30fps (N)	
	Video bit rate	32 kbps to 4 Mbps	
	Dual stream	Support	
	Stream type	Video, Video & Audio	
	Audio compression	G.711u	
	Audio bit rate	64 Kbps	
	Video and Audio	IP video input	1-ch (up to 5-ch) Up to 1080p resolution Support H.264+/H.264 IP cameras
Analog video input		4-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection	
Turbo HD input		1080p25, 1080p30, 720p25, 720p30	
AHD input		1080p25, 1080p30, 720p25, 720p30	
HDCVI input		1080p25, 1080p30, 720p25, 720p30	
CVBS input		Support	
HDMI/VGA output		1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
Audio input		1-ch RCA (2.0 Vp-p, 1 KΩ), and 4-ch via coaxial cable	
Audio output		1-ch, RCA (Linear, 1 kΩ)	
Two-way audio		Reuse the first audio input	
Synchronous playback		4-ch	
Network		Remote connection	32
		Network protocol	TCP/IP, PPPoE, DHCP, CTR-MAZi, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
	Network interface	1, RJ45 10 M/100 M self-adaptive Ethernet interface	
Auxiliary interface	SATA	1 SATA interface	
	Capacity	Up to 6 TB capacity for each disk	
	Alarm in/out	N/A	
	USB interface	Rear panel: 2 × USB 2.0	
General	Power supply	12 Vdc, 1.5 A	
	Consumption (without HDD)	≤ 8 W	
	Working temperature	-10 °C to 55 °C (14 °F to 131 °F)	
	Working humidity	10% to 90%	
	Dimension (W × D × H)	200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch)	
Weight (without HDD)	≤ 0.8 kg (1.8 lb)		

Physical Interface



No.	Description	No.	Description
1	Video and Audio in	6	LAN Network Interface
2	HDMI Interface	7	USB Interfaces
3	VGA Interface	8	GND
4	Audio OUT, RCA Connector	9	12 Vdc Power Input
5	Audio IN, RCA Connector		