

AVP-71SMIR

ANALOGUE DOME IR




KEY FEATURES

- Compact design
- 1.3M CMOS Sensor
- IR cut filter with auto switch
- Min. illumination: 0.1 Lux @F2.3 (0 Lux with IR)
- Auto white balance, auto gain control, electronic shutter control and backlight compensation
- Smart IR mode
- Internal Synchronization
- Advanced Engineering Design, High Reliability
- Patent universal adjustable structure provides convenient adjustment and high reliability



SPECIFICATION	AVP-71SMIR
Camera	
Image Sensor	1/3" 1.3M Sensor
Signal System	PAL/NTSC
Effective Pixels	1280 (H) × 960 (V)
Min. illumination	0.1 Lux @ (F1.2, AGC ON), 0 Lux with IR 0.3 Lux @ (F2.3, AGC ON), 0 Lux with IR
Shutter speed	PAL: 1/25 s to 1/10,000 s NTSC: 1/30 s to 1/10,000 s
Lens	3.6mm @ F2.3, Angle of view: 73.1°
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 85°, Rotation: 0 - 360°
Day & Night	IR cut filter with auto switch
Horizontal Resolution	720 TVL
Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62 dB
General	
Working Temperature/ Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10%
Power Consumption	Max. 1.5 W (Max. 4.5 W with IR cut filter on)
IR Range	Approx. 10 to 20 meters
Dimensions	Φ89.5 × 69.8 mm(Φ3.52" × 2.75")
Weight	200 g (0.44 lbs)



DIMENSIONS (mm)

