

Item code: 70337-IDH-21LIR

Product description: DOME camera VALUE Series

Main features: 2 MP IR Fixed Network Dome Camera, Colour: 0.01 Lux / (F1.2, AGC ON), 0.028 Lux / (F2.0, AGC ON), 3D DNS, BLC, IP67.


SPECIFICATIONS

Camera	
Image Sensor	1/2.8" progressive scan CMOS
Min. Illumination	Colour: 0.01 Lux@(F1.2, AGC ON), 0.028 Lux@(F2.0, AGC ON)
Shutter Speed	1/3 ÷ 1/100,000 s
Slow Shutter	Yes
Auto-Iris	No
Day & Night	IR cut filter
Digital Noise Reduction	3D-DNR
WDR	DWDR
Angle Adjustment	Pan: 0° ÷ 355°, tilt: 0° ÷ 75°
Lens	
Focal length	2.8 mm
Aperture	F2.0
Focus	Fixed
Field of View	Horizontal FOV 114.8° Vertical FOV 62° Diagonal FOV 135.5°
Lens Mount	M12
IR	
IR Range	Up to 30 m
Wavelength	850 nm
Compression Standard	
Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub stream: H.265/H.264/MJPEG
H.264 Type	Main Profile/High Profile/Baseline Profile
H.265 Type	Main Profile
Video Bit Rate	32 Kbps to 8 Mbps
Smart Feature-set	
Region of Interest	1 fixed region for main stream
Image	
Max. Resolution	1920 × 1080
Main Stream	50 Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720)
Max. Frame Rate	60 Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)


BS OHSAS 18001:2007
 Occupational Health and Safety Management System

ISO 9001:2015
 Quality Management System

ISO 14001:2015
 Environmental Management System

CI ITPI: 2015
 100% Made in Italy Certificate


MAZi – Brand distributed by **LINCE ITALIA S.p.A.**
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

Sub-stream Max. Frame Rate	50 Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60 Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Image Enhancement	BLC, 3D-DNR
Image Setting	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
Day/Night Switch	Auto, scheduled, day, night
Network	
Alarm Trigger	Motion detection, video tampering alarm, illegal login
Protocols	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, RTP, RTSP, RTCP, NTP, IGMP, QoS, UDP
General Function	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark
Firmware Version	V5.5.83
API	ONVIF (PROFILE S), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator, and User
Client	CMS-MAZi, CTR-MAZi
Web Browser	IE8+, Chrome 41.0-44, Firefox 30.0-51, Safari 8.0-11
Interface	
Communication Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
General	
Operating Conditions	-30 °C ÷ 60 °C (-22 °F ÷ 140 °F), humidity: 95% or less (non-condensing)
Power Supply	12 Vdc ± 25%, 5.5 mm coaxial power plug PoE (802.3af, class 3)
Power Consumption and Current	12 Vdc, 0.4 A, Max: 5 W PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, Max: 6.5 W
Ingress Protection	IP67, IK10
Material	<i>Bubble</i> : plastic <i>Front cover</i> : metal <i>Bottom base</i> : metal
Dimensions	<i>Camera</i> : Ø 111 × 82.4 mm (Ø 4.4" × 3.2") <i>With package</i> : 134 × 134 × 108 mm (5.3" × 5.3" × 4.3")
Weight	<i>Camera</i> : ~460 g (1 lb.) <i>With package</i> : ~660 g (1.5 lb.)