


## INVR-16L208H2



### Features and Functions

#### HD Input

- | H.265+/H.265/H.264+/H.264 video formats
- | Connectable to the third-party network cameras
- | Up to 16 IP cameras can be connected
- | Recording at up to 8 MP resolution
- | Supports live view, storage, and playback of the connected camera at up to 8 MP resolution

#### HD Output

- | HDMI and VGA independent outputs
- | HDMI Video output at up to 4K (3840 × 2160) resolution

#### HD Storage

- | 2 SATA interface connectable for recording and backup
- | H.265+ compression effectively reduces the storage space and costs by up to 75%

#### HD Transmission

- | 1 self-adaptive 10/100/1000 Mbps network interface

#### Various Applications

- | Centralized management of IP cameras, including configuration, information import/export, real-time information display, two-way audio, upgrade, etc.
- | Connectable to smart IP cameras and the recording, playing back, and backing up of VCA alarms can be realized
- | VCA detection alarm is supported
- | Instant playback for assigned channel during multi-channel display mode
- | Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- | CTR-MAZi for easy network management

### Video and Audio

IP video input	16-ch; Up to 8 MP resolution
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 kΩ)
Incoming bandwidth	160 Mbps
Outgoing bandwidth	80 Mbps
Recording resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/ 2CIF/CIF/ QCIF
HDMI output resolution	1-ch, 4K (3840 × 2160)/30 Hz, 1920 × 1080p/60 Hz, 1600 × 1200/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
VGA output resolution	1-ch, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Audio output	1-ch, RCA (linear, 1 kΩ)

### Decoding

Decoding format	H.265+/H.265/H.264+/H.264/MPEG4
Recording resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/2CIF/CIF/ QCIF
Synchronous playback	16-ch
Capability	4-ch @1080p, 1-ch @8 MP

### Network management

Network protocols	TCP/IP, DHCP, CTR-MAZi, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
-------------------	--

### External interface

USB interface	2 × USB 2.0
Network interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface

### Hard disk

SATA	1 SATA interfaces
Capacity	Up to 6 TB capacity for each disk

### General

Power supply	12 Vdc, 2.1 A
Power	≤ 15 W
Consumption (without hard disk)	≤ 10 W
Working temperature	-10 °C ÷ +55 °C (+14 ÷ +131 °F)
Working humidity	10% ÷ 90%
Chassis	1U
Dimensions (W × D × H)	385 × 315 × 52 mm (15.2"× 12.4" × 2.0")
Weight (without HDD)	≤ 1.8 kg (4.0 lb)