

IMVR-04A

IMVR-08A

IMVR-16A


NVR




KEY FEATURES

- Third-party network cameras supported
- Up to 2 Megapixels resolution recording
- HDMI and VGA output at up to 1920×1080P resolution
- HDD quota and group management
- 4/8 independent network interfaces for built-in switch


SPECIFICATION	IMVR-04A	IMVR-08A	IMVR-16A
Video/Audio input			
IP video input	4-ch	8-ch	16-ch
Two-way audio	1-ch, RCA (2.0 Vp-p, 1kΩ)		
Network			
Incoming bandwidth	25Mbps	50Mbps	100Mbps
Output bandwidth	40Mbps		
Remote connection	128		
Video/Audio output			
HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz		
Audio output	1-ch, RCA (Linear, 1kΩ).		
Decoding			
Live view / Playback resolution	1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF		
Capacity	4-ch@720P, 2-ch@1080P	8-ch@4CIF, 4-ch@720P, 2-ch@1080P	8-ch@4CIF, 8-ch@720P, 4-ch@1080P
Hard disk			
SATA	1 SATA interface for 1 HDD		
Capacity	Up to 4TB for each disk		
External interface			
Network interface	1 RJ-45 10 / 100 / 1000 Mbps self-adaptive Ethernet interface		1 RJ-45 10 / 100 Mbps selfadaptive Ethernet interface
Built-in switch network interface	4 independent 10 /100Mbps Ethernet interfaces	8 independent 10 /100 Mbps Ethernet interfaces	
USB interface	2 × USB 2.0		
Others			
Power supply	12V DC		
Consumption (without hard disk and PoE)	≤ 6 W	≤ 10 W	≤ 15 W
Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)		
Working humidity	10%~90%		
Chassis	1U chassis		
Dimensions (W × D × H)	205 × 205 × 45 mm	285 × 210 × 45 mm	
Weight	≤ 1 Kg (without hard disk)		



REAR PANEL



IMVR-04A



IMVR-08A / IMVR-16A

1. POWER SUPPLY
2. AUDIO IN
3. HDMI INTERFACE
4. LAN NETWORK INTERFACE
5. AUDIO OUT
6. VGA INTERFACE
7. USB INTERFACE
8. GROUND
9. BUILT-IN SWITCH ETHERNET INTERFACE