

Codice articolo: 1978-DSOG-P4000-U**Descrizione del prodotto:** sistema igienizzante plus

Caratteristiche principali: E' il sistema igienizzante più potente e veloce al mondo ideale per igienizzare grandi aree come depositi, ipermercati magazzini o anche per igienizzare obiettivi in spazi aperti. Emette, in un unico sparo, fino a 4000 m³ di fitta nebbia in 3 minuti. E' dotato di una sacca di liquido removibile (igienizzante Sani-FOG) ed è predisposto per l'utilizzo anche come nebbiogeno igienizzante (con sacca Dual-FOG, opzionale). E' predisposto per una facile installazione a parete (staffa inclusa), è dotato di un vano laterale per l'installazione di schede e accessori aggiuntivi.



CARATTERISTICHE TECNICHE

- Alimentazione: 230 Vca
- Consumo medio: 80 W
- Batteria di backup: presente
- Sistema di riscaldamento: Plus
- Copertura in un singolo sparo con funzionalità di igienizzante:
 - con sacca Sani-FOG: fino a 2.000 m³
 - con sacca Dual-FOG: fino a 4.000 m³
- Copertura in un singolo sparo con funzionalità di nebbiogeno antintrusione:
 - Con sacca Sani-FOG: non applicabile
 - Con sacca Dual-FOG (visibilità raccomandata): fino a 6.000 m³
 - Con sacca Dual-FOG (visibilità 1,5 m): fino a 4.000 m³
- Tempo max di emissione in un singolo sparo: 180 s
- Capacità totale di emissione con sacca carica:
 - con sacca Sani-FOG: 3.000 m³
 - con sacca Dual-FOG: 6.000 m³
- Numero di sacche incluse: 1
- Quantità di liquido nella sacca: 4.000 ml
- Caratteristiche dello sparo: programmabile in secondi
- Antimanomissione dell'ugello: presente
- Interfaccia seriale: presente
- Protocollo di comunicazione: standard
- Tempo di autonomia senza rete elettrica: ~ 5 h
- Tempo di riscaldamento da freddo: ~ 8 h
- Montaggio verticale: sì (staffa inclusa)
- Montaggio orizzontale: no
- Materiale: acciaio
- Peso: ~ 59 kg
- Dimensioni: 305 x 440 x 435 mm

ACCESSORI DISPONIBILI

- **1982-D-FBP4000** • Fluid bag Dual-FOG da 4.000 ml per modello Power
- **1984-S-FBP4000** • Fluid bag Sani-FOG da 4.000 ml per modello Power

**BS OHSAS 18001: 2007**
Occupational Health and
Safety Management System**ISO 14001: 2015**
Environmental Management
System**ISO 9001: 2015**
Quality Management
System**CI ITP: 2015**
100% Made in Italy
Certificate**LINCE ITALIA S.p.A.**Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

Item Code: 1978-SFOG-P4000-U**Product description:** Hygienizing system plus

Main features: It is the most powerful and fastest hygienizing system in the world, ideal for hygienizing large areas such as storage areas, hypermarkets, warehouses or even for hygienizing targets in open spaces. In a single shot it provides up to 4,000 m³ of dense fog in 3 minutes. It is equipped with a removable fluid bag (hygienizing liquid, Sani-FOG) and is designed to be used also as hygienizing fogging system (with Dual-FOG fluid bag, optional). It is designed for easy wall installation (bracket included), it has a side compartment for the installation of additional boards and accessories.



SPECIFICATIONS

- Power supply: 230 Vac
- Average consumption: 80 W
- Backup battery: present
- Heating system: Plus
- Coverage in a single shot with hygienizing functionality
 - with Sani-FOG fluid bag: up to 2,000 m³
 - with Dual-FOG fluid bag: fino a 4,000 m³
- Coverage in a single shot with fogging functionality
 - with Sani-FOG fluid bag: not applicable
 - with Dual-FOG fluid bag (1.5 m visibility): up to 6,000 m³
 - with Dual-FOG fluid bag (recommended visibility): up to 4,000 m³
- Max emission time in a single shot: 180 s
- Total emission capacity with loaded bag:
 - with Sani-FOG fluid bag: up to 3,000 m³
 - with Dual-FOG fluid bag: fino a 6,000 m³
- Number of bags included: 1
- Quantity of liquid in the bag: 4,000 ml
- Shooting characteristics: programmable in seconds
- Nozzle anti-tamper: present
- Serial interface: present
- Communication protocol: standard
- Autonomy time without mains: ~ 5 h
- Heating time from cold: ~ 8 h
- Vertical mounting: yes (bracket included)
- Horizontal mounting: no
- Cabinet material: steel
- Weight: 59 kg
- Dimensions: 305 x 440 x 435 mm

AVAILABLE ACCESSORIES

- **1982-D-FBP4000** • 4,000 ml Dual-FOG fluid bag for Power model
- **1984-S-FBP4000** • 4,000 ml Sani-FOG fluid bag for Power model

**BS OHSAS 18001: 2007**
Occupational Health and
Safety Management System**ISO 14001: 2015**
Environmental Management
System**ISO 9001: 2015**
Quality Management
System**CI ITP: 2015**
100% Made in Italy
Certificate**LINCE ITALIA S.p.A.**

Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 2 di 2