



IVN-44EVR

4 MP IP Turret varifocal camera, 2.8~12 mm lens, PoE, 3 pcs array IR, 30 m, Colour 0.01 Lux, Hardware reset, 1 ch audio I/O, PoE, IP67 metal case.

1/2.9" low-light CMOS sensor

Support 1 ch Audio I/O and hardware reset

Support H.264/H.265/H.265+ video compression standard, dual stream

Max resolution 2592×1944 @25fps

Support Onvif and P2P

Support ICR switching

3 pcs Array IR, Max 30 m

2.8 ~ 12 mm lens

IP67 full metal case with junction box

12 Vdc/PoE, 500 mA

Camera

DSP	Mstar SSC377D
Image Sensor	1/2.9", 4 MP CMOS GC4653
Min. Illumination	Colour 0.01 Lux
Signal to noise ratio	≥ 50 dB

Video

Video processing	H.265+/H.265/H.264 video encoding code stream 0.1 ~ 8 Mbps adjustable; frame 1-25 fps adjustable
------------------	--

Audio

Audio Port	One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom
------------	--

Network

Network Interface	One RJ45, 10/100 M adaptive Ethernet interface 2 kV lightning protection
Protocol Support	Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, RTMP and multiple private NVR protocols
Intelligent Functions	IE6.0 and above (Web Server embedded in the device) browser use; Motion detection and OSD customization; Humanoid detection; P2P cloud service; Support mobile web access; Support IP filtering

Image

Image Resolution	<i>Main stream:</i> 25fps @(2592×1944); 30fps @(2560×1440, 2304×1296, 1080P, 720P, 1920×1920, 1200×1200) <i>Sub stream:</i> 30fps @(D1, VGA, 640×360, 480×360, GIF, 480×480); Support CBR/VBR
------------------	---

General

Mobile client	Support Windows Mobile, iPhone, iPad, Android
Business functions	Support IE6.0 and above (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit
Work Environment	-30 °C ÷ +85 °C
Camera Dimension (DxH)	145 x 107.86 mm