



IWN-44EVR

IP Bullet camera 4 MP, 2.8 ~ 12 mm lens, 5 pcs Array IR, Max 40 m, 12 Vdc/PoE, dual stream, 1 ch Audio I/O and hardware reset, IP67 metal bullet case.

1/3" low-light CMOS sensor
Support 1 ch Audio I/O and hardware reset
Support H.264/H.265/H.265+ video compression standard, dual stream
Max resolution: 2592x1944 @25fps
Support Onvif and P2P
Support ICR switching
5 pcs Array IR, Max 40 m
2.8 ~ 12 mm lens
IP67 metal bullet case
Power supply: 12 Vdc/PoE, 500 mA

Camera	
DSP	Mstar SSC377D
Image Sensor	1/3", 4 MP CMOS GC4653
Min. Illumination	Colour 0.01 Lux
Signal to noise ratio	≥ 50 dB
Video	
Video processing	H.265+/H.265/H.264 video encoding, code stream 0.1~8 Mbps adjustable; frame 1-25fps adjustable
Audio	
Audio Port	One audio input One audio output, G711U/G711A/ACC encoding, support simplex two-way voice intercom
Network	
Network Interface	One RJ45, 10/100 M adaptive Ethernet interface 2 kV lightning protection
Protocol Support	Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, RTMP and multiple private NVR protocols
Humanoid detection	Support
Intelligent Functions	IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization Humanoid detection P2P cloud service Support mobile web access Support IP filtering
Image	
Image Resolution	<i>Main stream:</i> 25fps@ (2592×1944); 30fps @ (2560×1440, 2304×1296, 1080P, 720P, 1920x1920, 1200x1200) <i>Sub stream:</i> 30fps @ (D1, VGA, 640×360, 480x360, GIF, 480x480) Support CBR/VBR
General	
Mobile client	Support Windows Mobile, iPhone, iPad, Android
Business Functio	Support IE6.0 and above (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit
Work Environment	-30 °C ÷ +85 °C
Camera Dimension (LxWxH)	280 x 84 x 84 mm

