

Codice articolo: 1972-DFOG-P500-U**Descrizione del prodotto:** sistema nebbiogeno igienizzante

Caratteristiche principali: Nebbiogeno potente e veloce, ideale per proteggere aree di piccole/medie dimensioni come negozi, appartamenti, bancomat. In generale può essere utilizzato in tutte le applicazioni professionali in cui è richiesta per la sicurezza una tecnologia superiore. Emette, in un unico sparo, fino a 500 m³ di fitta nebbia in 30 secondi. E' dotato di una sacca di liquido nebbiogeno igienizzante ed è predisposto per una facile installazione a parete; è dotato di un vano nella parte inferiore per l'installazione di schede e accessori aggiuntivi.

**CARATTERISTICHE TECNICHE**

- Alimentazione: 230 Vca
- Consumo medio: 42 W
- Batteria di backup: presente
- Sistema di riscaldamento: Plus
- Copertura in un singolo sparo (visibilità 1,5 m): fino a 750 m³
- Copertura in un singolo sparo (visibilità raccomandata): fino a 500 m³
- Tempo max di emissione in un singolo sparo: 30 s
- Capacità totale di emissione con sacca carica: 1.500 m³
- Numero di sacche incluse: 1
- Quantità di liquido nella sacca: 1.000 ml
- Caratteristiche dello sparo: programmabile in secondi
- Antimanomissione dell'ugello: presente
- Interfaccia seriale: presente
- Protocollo di comunicazione: standard
- Tempo di autonomia senza rete elettrica: ~ 2 h
- Tempo di riscaldamento da freddo: ~ 70 min
- Montaggio verticale: possibile
- Montaggio orizzontale: possibile
- Materiale: acciaio
- Peso: 16 kg
- Dimensioni: 215 x 270 x 435 mm

ACCESSORI DISPONIBILI

- **1981-D-FBP1000** • Fluid bag Dual-FOG da 1.000 ml per modello Power
- **1983-S-FBP1000** • Fluid bag Sani-FOG da 1.000 ml per modello Power

**BS OHSAS 18001:2007**
Occupational Health and
Safety Management System**ISO 14001:2015**
Environmental Management
System**ISO 9001:2015**
Quality Management
System**CI ITP: 2015**
100% Made in Italy
Certificate**LINCE ITALIA S.p.A.**Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

Item Code: 1972-DFOG-P500-U**Product description:** Hygienizing fogging system

Main features: Powerful and fast hygienizing fogging system, ideal for protecting small/medium-sized areas such as shops, apartments, ATMs and in general can be used in all professional applications where superior technology is required for security. In a single shot it provides up to 500 m³ of dense fog in 30 seconds. It is equipped with a removable fluid bag and is designed for easy wall installation; it has a compartment at the bottom for the installation of additional boards and accessories.

**SPECIFICATIONS**

- Power supply: 230 Vac
- Average consumption: 42 W
- Backup battery: present
- Heating system: Plus
- Coverage in a single shot (visibility 1.5 m): up to 750 m³
- Coverage in a single shot (recommended visibility): up to 500 m³
- Max emission time in a single shot: 30 s
- Total emission capacity with loaded bag: 250 m³
- Number of bags included: 1
- Quantity of liquid in the bag: 1,000 ml
- Shooting characteristics: programmable in seconds
- Nozzle anti-tamper: present
- Serial interface: present
- Communication protocol: standard
- Autonomy time without mains: ~ 2 h
- Heating time from cold: ~ 70 min
- Vertical mounting: possible
- Horizontal mounting: possible
- Cabinet material: steel
- Weight: 16 kg
- Dimensions: 215 x 270 x 435 mm

AVAILABLE ACCESSORIES

- **1981-D-FBP1000** • 1,000 ml Dual-FOG fluid bag for Power model
- **1983-S-FBP1000** • 1,000 ml Sani-FOG fluid bag for Power model

**BS OHSAS 18001: 2007**
Occupational Health and
Safety Management System**ISO 14001: 2015**
Environmental Management
System**ISO 9001: 2015**
Quality Management
System**CI ITP: 2015**
100% Made in Italy
Certificate**LINCE ITALIA S.p.A.**Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 2 di 2