

**Codice articolo:** 1976-SFOG-P500-U**Descrizione del prodotto:** sistema igienizzante plus

**Caratteristiche principali:** Sistema igienizzante potente e veloce, ideale per proteggere aree di piccole/medie dimensioni come negozi, appartamenti, bancomat e in generale adatto a tutte le applicazioni professionali in cui è richiesta per la sicurezza una tecnologia superiore. Emette, in un unico sparo, fino a 250 m<sup>3</sup> di fitta nebbia in 30 secondi. E' dotato di una sacca di liquido (igienizzante Sani-FOG) ed è predisposto per l'utilizzo anche come nebbiogeno igienizzante (con sacca Dual-FOG, opzionale) ed una facile installazione a parete; è dotato di un vano nella parte inferiore per l'installazione di schede e accessori aggiuntivi.



#### CARATTERISTICHE TECNICHE

- Alimentazione: 230 Vca
- Consumo medio: 42 W
- Batteria di backup: presente
- Sistema di riscaldamento: Plus
- Copertura in un singolo sparo con funzionalità di igienizzante:
  - con sacca Sani-FOG: fino a 250 m<sup>3</sup>
  - con sacca Dual-FOG: fino a 500 m<sup>3</sup>
- Copertura in un singolo sparo con funzionalità di nebbiogeno antintrusione:
  - Con sacca Sani-FOG: non applicabile
  - Con sacca Dual-FOG (visibilità raccomandata): fino a 750 m<sup>3</sup>
  - Con sacca Dual-FOG (visibilità 1,5 m): fino a 500 m<sup>3</sup>
- Tempo max di emissione in un singolo sparo: 30 s
- Capacità totale di emissione con sacca carica:
  - con sacca Sani-FOG: 750 m<sup>3</sup>
  - con sacca Dual-FOG: 1.500 m<sup>3</sup>
- Numero di sacche incluse: 1
- Quantità di liquido nella sacca: 1.000 ml
- Caratteristiche dello sparo: programmabile in secondi
- Antimanomissione dell'ugello: presente
- Interfaccia seriale: presente
- Protocollo di comunicazione: standard
- Tempo di autonomia senza rete elettrica: ~ 2 h
- Tempo di riscaldamento da freddo: ~ 70 min
- Montaggio verticale: possibile
- Montaggio orizzontale: possibile
- Materiale: acciaio
- Peso: 16 kg
- Dimensioni: 215 x 270 x 435 mm

#### ACCESSORI DISPONIBILI

- **1981-D-FBP1000** • Fluid bag Dual-FOG da 1.000 ml per modello Power
- **1983-S-FBP1000** • Fluid bag Sani-FOG da 1.000 ml per modello Power

**BS OHSAS 18001:2007**  
Occupational Health and  
Safety Management System**ISO 14001:2015**  
Environmental Management  
System**ISO 9001:2015**  
Quality Management  
System**CI ITPI: 2015**  
100% Made in Italy  
Certificate**LINCE ITALIA S.p.A.**Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia  
Tel.: +39 06 92928252 - Fax: +39 06 92942586[www.lince.net](http://www.lince.net) – [info@lince.net](mailto:info@lince.net)  
**MD-03.11 Rev. 6 - Pag.: 1 di 2**

**Item Code:** 1976-SFOG-P500-U**Product description:** Hygienizing system plus

**Main features:** Powerful and fast hygienizing system plus, ideal for protecting small/medium-sized areas such as shops, apartments, ATMs and in general can be used in all professional applications where superior technology is required for security. In a single shot it provides up to 250 m<sup>3</sup> of dense fog in 30 seconds. It is equipped with a removable fluid bag (hygienizing liquid, Sani-FOG) and is designed to be used also as hygienizing fogging system (with Dual-FOG fluid bag, optional) and for easy wall installation; it has a compartment at the bottom for the installation of additional boards and accessories.



### SPECIFICATIONS

- Power supply: 230 Vac
- Average consumption: 42 W
- Backup battery: present
- Heating system: Plus
- Coverage in a single shot with hygienizing functionality
  - *with Sani-FOG fluid bag*: up to 250 m<sup>3</sup>
  - *with Dual-FOG fluid bag*: fino a 500 m<sup>3</sup>
- Coverage in a single shot with fogging functionality
  - *with Sani-FOG fluid bag*: not applicable
  - *with Dual-FOG fluid bag* (1.5 m visibility): up to 750 m<sup>3</sup>
  - *with Dual-FOG fluid bag* (recommended visibility): up to 500 m<sup>3</sup>
- Max emission time in a single shot: 30 s
- Total emission capacity with loaded bag:
  - *with Sani-FOG fluid bag*: up to 750 m<sup>3</sup>
  - *with Dual-FOG fluid bag*: fino a 1,500 m<sup>3</sup>
- Number of bags included: 1
- Quantity of liquid in the bag: 1,000 ml
- Shooting characteristics: programmable in seconds
- Nozzle anti-tamper: present
- Serial interface: present
- Communication protocol: standard
- Autonomy time without mains: ~ 2 h
- Heating time from cold: ~ 70 min
- Vertical mounting: possible
- Horizontal mounting: possible
- Cabinet material: steel
- Weight: 16 kg
- Dimensions: 215 x 270 x 435 mm

### AVAILABLE ACCESSORIES

- **1981-D-FBP1000** • 1,000 ml Dual-FOG fluid bag for Power model
- **1983-S-FBP1000** • 1,000 ml Sani-FOG fluid bag for Power model

**BS OHSAS 18001:2007**  
Occupational Health and  
Safety Management System**ISO 14001:2015**  
Environmental Management  
System**ISO 9001:2015**  
Quality Management  
System**CI ITPI: 2015**  
100% Made in Italy  
Certificate**LINCE ITALIA S.p.A.**Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia  
Tel.: +39 06 92928252 - Fax: +39 06 92942586[www.lince.net](http://www.lince.net) – [info@lince.net](mailto:info@lince.net)  
**MD-03.11 Rev. 6 - Pag.: 2 di 2**