

**Item code:** 70412-HXVR-08L104H2

**Product description:** DVR VALUE Series

**Main features:** TURBO HD DVR 8 Channels: Support H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression. HDTVI input: 8 MP, AHD input: 5 MP, HDCVI input: 5 MP, CVBS input: PAL/NTSC, Audio IN/Out: 4/1, Serial interface: RS-485 (half-duplex), USB interface: Front panel: 1 Å~ USB 2.0; Rear panel: 1 Å~ USB 3.0, Power supply: 12 Vdc.



### SPECIFICATIONS

Recording	
<b>Video compression</b>	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
<b>Encoding resolution</b>	<i>When 8 MP Lite mode is not enabled:</i> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF <i>When 8 MP Lite mode is enabled:</i> 8 MP Lite/5 MP/4 MP/3MP/1080P/720P/WD1/4CIF/VGA/CIF
<b>Frame rate</b>	<b>Main stream:</b> <i>When 8 MP Lite mode is not enabled:</i> 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) *: 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K2  <i>When 8 MP Lite mode enabled:</i> 8 MP Lite/5 MP@12 fps/4 MP/3MP/1080P/720P/WD1/4CIF/VGA/CIF@15 fps *: 8 MP Lite is only available for DS-7204HUHI-K2  <b>Sub-stream:</b> WD1/4CIF/CIF@25 fps (P)/30fps (N)
<b>Video bit rate</b>	32 Kbps to 10 Mbps
<b>Dual stream</b>	Support
<b>Stream type</b>	Video, Video & Audio
<b>Audio compression</b>	G.711u
<b>Audio bit rate</b>	64 Kbps
Video and Audio	
<b>IP video input</b>	8-ch (up to 16-ch) Up to 8 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
<b>Analog video input</b>	8-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
<b>HDTVI input</b>	8 MP, 5 MP, 4 MP, 3 MP, 1080 p 30, 1080 p 25, 720 p 60, 720 p 50, 720 p 30, 720 p 25
<b>AHD input</b>	5 MP, 4 MP, 1080 p 25, 1080 p 30, 720 p 25, 720 p 30
<b>HDCVI input</b>	5 MP, 4 MP, 1080 p 25, 1080 p 30, 720 p 25, 720 p 30
<b>CVBS input</b>	PAL/NTSC
<b>CVBS output</b>	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480


**BS OHSAS 18001:2007**  
 Occupational Health and  
 Safety Management System

**ISO 9001:2015**  
 Quality Management  
 System

**ISO 14001:2015**  
 Environmental Management  
 System

**CI IPTI: 2015**  
 100% Made in Italy  
 Certificate


**MAZi** – Brand distributed by **LINCE ITALIA S.p.A.**  
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia  
 Tel.: +39 06 92928252 - Fax: +39 06 92942586

[www.lince.net](http://www.lince.net) – [info@lince.net](mailto:info@lince.net)  
**MD-03.11 Rev. 6 - Pag.: 1 di 2**

<b>VGA output</b>	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
<b>HDMI output</b>	1-ch, 4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
<b>Audio input</b>	4-ch, RCA (2.0 Vp-p, 1 KΩ)
<b>Audio output</b>	1-ch, RCA (Linear, 1 KΩ)
<b>Two-way audio</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)
<b>Synchronous playback</b>	8-ch
<b>Network</b>	
<b>Remote connection</b>	64
<b>Network protocol</b>	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
<b>Network interface</b>	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
<b>Auxiliary Interface</b>	
<b>SATA</b>	2 SATA interfaces
<b>Capacity</b>	Up to 10 TB capacity for each disk
<b>Serial interface</b>	RS-485 (half-duplex)
<b>USB interface</b>	<i>Front panel:</i> 1 × USB 2.0 <i>Rear panel:</i> 1 × USB 3.0
<b>Alarm in/out</b>	8/4
<b>General</b>	
<b>Power supply</b>	12 Vdc, 3,33 A
<b>Consumption (without HDD)</b>	≤ 20 W
<b>Working temperature</b>	-10 °C ÷ 55 °C (14 °F ÷ 131 °F)
<b>Working humidity</b>	10% ÷ 90%
<b>Dimension (W × D × H)</b>	380 × 320 × 48 mm (7.9" × 7.9" × 1.9")
<b>Weight (without HDD)</b>	≤ 1.78 kg (3.9 lb)



**BS OHSAS 18001:2007**  
Occupational Health and  
Safety Management System



**ISO 9001:2015**  
Quality Management  
System



**ISO 14001:2015**  
Environmental Management  
System



**CI ITPI: 2015**  
100% Made in Italy  
Certificate



**MAZi – Brand distributed by LINCE ITALIA S.p.A.**  
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia  
Tel.: +39 06 92928252 - Fax: +39 06 92942586  
[www.lincede.net](http://www.lincede.net) - [info@lincede.net](mailto:info@lincede.net)  
**MD-03.11 Rev. 6 - Pag.: 2 di 2**